

CORDPLAST®

THERMOCORD SILICONE 300°C-2S

|  |  |  |  |  |
|---|---|---|---|---|
| mm | gr/mt | Bar* | Mm/ca* | mm |
| 19 | 110 | 3.0 | 7300 | 9 |
| 25 | 185 | 2.8 | 7100 | 12 |
| 38 | 305 | 2.6 | 6000 | 18 |
| 51 | 360 | 2.6 | 5200 | 24 |
| 63 | 485 | 2.4 | 4600 | 31 |
| 76 | 580 | 2.2 | 4300 | 38 |
| 89 | 690 | 2.0 | 4000 | 44 |
| 95 | 730 | 1.9 | 3700 | 49 |
| 102 | 770 | 1.9 | 3500 | 52 |
| 114 | 845 | 1.5 | 3000 | 60 |
| 127 | 925 | 1.4 | 2400 | 69 |
| 152 | 1200 | 1.2 | 1700 | 75 |
| 178 | 1430 | 1.0 | 1200 | 90 |
| 203 | 1650 | 0.7 | 900 | 101 |
| 254 | 2090 | 0.5 | 700 | 150 |
| 305 | 2550 | 0.3 | 500 | 200 |

A richiesta è possibile fornire: versione autoestinguente V-0 (UL 94).
Blu o grigio



IMPIEGO

Tubo flessibile realizzato con doppio strato di tessuto in fibra di vetro spalmato di silicone, spirale incorporata in filo di acciaio armonico ramato, doppio cordoncino esterno in fibra di vetro. Aspirazione, estrazione e soffiaggio d'aria anche con particelle polverose in presenza di alte temperature.



COLORE

Rosso mattone.

COMPRESSIBILITA' ASSIALE

30%

DIAMETRI DI PRODUZIONE

19 - 25 - 28 - 30 - 32 - 35 - 38 - 39 - 41 - 44 -
51 - 55 - 57 - 60 - 63 - 64 - 65 - 70 - 76 - 80 -
83 - 90 - 95 - 102 - 114 - 120 - 127 - 130 - 140 -
152 - 160 - 165 - 170 - 180 - 203 - 229 - 254 -
305



TEMPERATURA

-60°C / +270°C, con punte fino a 300°C
-76°F / +518°F F



LUNGHEZZA

mt 4

SATI GROUP S.P.A.

Via C. Bonazzi, 24 - 40013 CASTEL MAGGIORE (BO) - ITALY

Tel. +39.051.700321 - Fax +39.051.701350

E-mail: commerciale@satigroup.it

web: www.satigroup.it