







CORDPLAST®

VINOREX FOR WINE



					
mm	mm	gr/mt	bar	bar	mm
20	3	335	28	0.9	100
25	3	400	24	0.9	125
30	3.5	535	21	0.9	150
32	3.5	580	21	0.9	160
35	3.7	630	21	0.9	175
38	3.7	680	21	0.9	190
40	3.7	710	21	0.9	200
45	4.2	815	21	0.9	225
51	5.0	1165	17	0.95	300
60	5.5	1550	17	0.95	360
63	5.6	1700	17	0.95	378
70	5.7	1845	14	0.95	420
76	6.0	1940	14	0.95	450
80	6.4	2135	14	0.95	480
90	6.7	2425	14	0.95	540
102	7.2	3200	12	0.95	600
110	7.7	3590	12	0.9	660
120	7.8	3880	12	0.9	720
152	8.7	6100	10.5	0.9	900

TEMPERATURE, TEMPERATUR, TEMPERATURA, TEMPERATURE :

-5°C / +60°C +23°F / +140°F

NORMS, NORMEN, NORMAS, NORMES: REG. UE 10/2011, FOR SIMULANT TYPE A-B-C, ISO 1307

LENGHT/LANGE/LONGITUD/LONGUEUR: mt 50 up to Ø 80 - mt 25 up to Ø 90 and over



Construction: strong, flexible, and smooth non-toxic plasticized pvc. Shock resistant pvc spiral.

Cover: crushing, abrasion and weather resistant, light corrugated outside.

Application: for delivery of mineral waters, fruit juices, wines, liqueurs up to 15% alcohol contents alimentary liquids etc.



Konstruktion: stabiler, hochflexibler, innen glatter, toxidenfrei, plastifizierter pvc. Verstärkungsspirale aus schlag- und

Druckfestem: pvc. Äusserst strapazierfähig, biegsam, druck- abriebfest, uv- und

Decke: witterungsbeständig, leicht gewellte aussendecke

Anwendung: für entladen von mineralwasser, fruchtsäften, weinen, flüssigen nahrungsmitteln bis zu 15% alkoholgehalt



Construcción: manguera lisa, no tóxica, ligera y flexible en pvc plastificado, espiral de refuerzo en pvc rígido anti choque y antideformante.

Cobertura: externa semilisa, resistente a cargas, abrasión y agentes atmosféricos.

Uso: para suministro de aguas minerales, jugos de fruta, líquidos comestibles, vinos, licores con contenido alcoholico hasta el 15% etc.



Construction: tuyau lisse et flexible en pvc souple non toxique. Spire en pvc rigide antichoc

Revetement: surface semi-ondulee resistente a l'abrasion, les agents atmosferiques, ecrasement et la plupart des produits chimiques.

Application: refoulement d'eau, liquides, jus de fruits, bieres, vins, liqueurs et alcool jusqu'a 15% etc.

SATI GROUP S.P.A.

Via C. Bonazzi, 24 - 40013 CASTEL MAGGIORE (BO) - ITALY

Tel. +39.051.700321 - Fax +39.051.701350

E-mail: export@satigroup.it

web: www.satigroup.it