



L/AP

ANTIPOLVERE 2 LATI IMPRESSIONE TELA
DUST SEALING CLOTH



- Altamente resistente all'ozono ed ai raggi ultravioletti, ultra flessibile.

High resistance against ozone and ultraviolet radiations, extremely flexible.



IMPIEGO APPLICATIONS

Altamente resistente all'ozono ed ai raggi ultravioletti, ultra flessibile, serve ad abbattere polveri su qualsiasi macchinario come ad esempio il telaio superiore di un vaglio, sopra i nastri trasportatori, gli alimentatori, gli scivoli, etc. La miscela fornisce resistenza all'invecchiamento e non si deteriora quando soggetto a vibrazioni costanti.

Superficie: I.T./I.T.

Highly resistance against ozone and ultraviolet radiations, extremely flexible. Recommended for dust abatement on screeners, conveyor belts, loaders and chutes. Highly resistant ageing compound, high deteriorating resistance if subjected to steady vibrations.

Surface: I.T./I.T.



mm

2



STOCK

1

✓



m

1,5



m

20



DUREZZA
HARDNESS



CARICO ROTTURA
TENSILE STRENGTH



ALLUNGAMENTO
ELONGATION



LACERAZIONE
TEAR

Norme / Norms:
ASTM D2240

Norme / Norms:
ASTM D412

Norme / Norms:
ASTM D412

Norme / Norms:
ASTM D624

40 Shore A ± 5

150 kg/cm²

550%

60 kg/cm



1,0 gr/cm³



-25°C / +70°C
-13°F / +158°F