



- **VERY LIGHT**
- **LOW COST**



IMPIEGO / USE / EMPLOI / EINSATZ / EMPLEO

Idoneo per mandata di carburanti, diesel eco e benzina verde.

Suitable for the delivery of fuel, including eco diesel and unleaded gasoline.

Convenable pour le refoulement des carburants, diesel eco et essence sans plomb inclus.

Geeignet für die Lieferung von Kraftstoffen, Öko-Diesel und bleifreiem Benzin.

Adecuado para la entrega de carburantes, eco diesel y gasolina sin plomo incluidos.



STRUTTURA / STRUCTURE / STRUCTURE STRUKTUR / ESTRUCTURA

SOTTOSTRATO

INNER LAYER
COUCHE INTÉRIEURE
SCHLAUCHEINLAGE
CAPA INTERIOR

Liscio in PVC trasparente, antiolio anche per eco diesel e benzina verde.

PVC smooth, transparent, oil resistant, including eco diesel and unleaded gasoline.

En PVC lisse, transparent, résistant aux carburants, diesel eco et essence sans plombs inclus.

Glatt aus transparentem PVC, ölbeständig, ebenso gegen Öko-Diesel und bleifreies Benzin.

En PVC liso, transparente, resistente a los carburantes, eco diesel y gasolina sin plomo incluidos.

INSERTI

REINFORCEMENT
RENFORCEMENT
EINLAGEN
REFUERZOS

Tessili sintetici ad alta resistenza.

High tenacity synthetic textile yarns.

Gâines synthétiques textiles de haute ténacité.

Hochfeste synthetische Textilgarne.

Hilos sintéticos textiles de alta tenacidad.

COPERTURA

OUTER COVER
COUCHE EXTERIEURE
AUSSENSCHICHT
CAPA EXTERIOR

In PVC nera opaca, resistente agli olii, olii eco e agenti atmosferici. **Superficie:** liscia estrusa.

Black PVC opaque, smooth, oil, green fuel and weathering resistant. **Outer layer:** smooth extruded.

En PVC noir opaque, lisse, résistant aux carburants, carburants éco et aux agents atmosphériques. **Couche extérieure:** lisse extrudée.

Aus mattschwarzem PVC, beständig gegen Öle, Öko-öle und Witterungseinflüsse. **Oberfläche:** extrudiert glatt.

En PVC negro opaco, resistente a los carburantes, carburantes eco y agentes atmosféricos. **Capa exterior:** lisa extruido.

IMBALLO: polietilene trasparente **PACKAGING:** transparent polyethylene

EMBALLAGE: polyéthylène transparent **VERPACKUNG:** transparentes Polyethylen

EMBALAJE: polietileno transparente

					
mm	mm	bar	bar	g/m	mt
5	10.5	10	30	80	25
6	11	10	30	80	25
8	14	10	30	110	25
10	16	10	30	140	25



Sottostrato
Inner layer
Couche Intérieure
Schlaucheinlage
Capa interior



Inserti
Reinforcement
Renforcement
Einlagen
Refuerzos



Copertura
Outer Cover
Couche extérieure
Außenschicht
Capa exterior



-4°C / +60°C
+23°F / +140°F