SATIHOSE

FLOSTER EPDM / HD
2-TONE NATURAL RUBBER

- **Copertura particolarmente resistente ad agenti atmosferici.**
  Wear resistant cover.

IMPIEGO
APPLICATIONS

Utilizzata comunemente come rivestimento di tamburi metallici nel settore dei nastri trasportatori, o come protezione di superfici metalliche. Particolarmente indicata per offrire una discreta resistenza all'abrasione ed alla lacerazione, discrete caratteristiche fisico meccaniche.

Commonly used as a coating on metal drums in the conveyor belt sector or to protect metal surfaces. In particular, it is indicated to offer fair resistance against abrasion and laceration. It has fair physical and mechanical characteristics.

STRUTTURA
BODY

A **Materiale** Material	Tubo prodotto su mandrino bistrato; Sottostrato in gomma naturale (NR) copertura in gomma BR/EPDM di colore nero. Abrasion resistant 2 tone natural rubber light brown inside black outside.
B **Inserti** Reinforcement	---
Superfice Surface	Liscia ad impressione tela. Smooth with fabric impression.
Colore Color	Interno nocciola chiaro, esterno nero. Light hazelnut interior, black exterior.
Durezza Hardness	45 shore a ± 5
Carico di rottura Breaking strenght	150 kg/cm²
Allungamento a rottura Breaking elongation	400%

mm	mm	bar	kg/mt	mm	m
50 × 58	4	-	0,75	-	12
60 × 68	4	-	0,88	-	12
70 × 78	4	-	1,02	-	12
76 × 84	4	-	1,07	-	12
80 × 88	4	-	1,16	-	12
90 × 98	4	-	1,27	-	12
102 × 110	4	-	1,44	-	12
114 × 122	4	-	1,60	-	12
120 × 128	4	-	1,68	-	12
130 × 138	4	-	1,83	-	12
140 × 148	4	-	1,95	-	12
152 × 160	4	-	2,11	-	12
168 × 176	4	-	2,32	-	12
193 × 201	4	-	2,68	-	9
200 × 208	4	-	2,76	-	12
220 × 228	4	-	3,03	-	6
254 × 262	4	-	3,50	-	12
273 × 281	4	-	3,74	-	10
305 × 313	4	-	4,20	-	12
323 × 331	4	-	4,42	-	6
350 × 358	4	-	4,81	-	6
400 × 408	4	-	5,52	-	7
508 × 516	4	-	6,81	-	6
612 × 620	4	-	8,50	-	6

FASCETTE E COLLARI STRINGITUBO CONSIGLIATE
RECOMMENDED CLAMP/COLLAR

STC - Fascette con bullone Hose clamps with bolt **(pag. 213-215)**

NORME NORMS:
ISO 1307

CONFEZIONAMENTO BOX:
ROTOLI TAGLIATI A MISURA
ROLLS CUT TO SIZE

-40°C / +70°C
-40°F / +158°F