




IMPIEGO APPLICATIONS

Macchine agricole	Agriculture machine
Edilizia	Construction
Irrigazione	Irrigation
Automotive	Automotive



DESCRIZIONE DESCRIPTION

Fascetta ad altissima tenuta, compatta e resistente. La banda interna liscia ed i bordi rialzati, conferiscono assoluta sicurezza al tubo, conforme alla normativa DIN 3017.

High resistant clamp, compact and durable. Rolle-up band edges and smooth band underside are able to guarantee total protection to the hose. Conforme to DIN 3017.



MATERIALE MATERIAL

Banda Band	Acciaio inossidabile Stainless steel AISI 430
Cassetto Housing	Acciaio inossidabile Stainless steel AISI 430
Vite Screw	Acciaio zincato Zinc-plated steel

LARG. NASTRO BAND WIDTH	DIAM. DIAM.	SPESSORE THICKNESS	COPPIA DI SERRAGGIO RACCOMANDATA RECOMMENDED TIGHTENING TORQUE (PAG. 221)	SCATOLE BOX
A	B	C	Nm	pz/nrm

9
mm

W2A09008012000	9	8-12	0,8	2,6	100
W2A09010016000	9	10-16	0,8	2,6	100
W2A09012020000	9	12-20	0,8	2,6	100
W2A09016025000	9	16-25	0,8	4,0	100
W2A09016027000	9	16-27	0,8	4,0	100
W2A09020032000	9	20-32	0,8	4,0	100
W2A09025040000	9	25-40	0,8	4,0	100
W2A09035050000	9	32-50	0,8	4,0	50
W2A09040060000	9	40-60	0,8	4,0	50
W2A09050070000	9	50-70	0,8	4,0	50
W2A09060080000	9	60-80	0,8	4,0	50
W2A09070090000	9	70-90	0,8	4,0	25
W2A09080100000	9	80-100	0,8	4,0	25
W2A09090110000	9	90-110	0,8	4,0	25
W2A09100120000	9	100-120	0,8	4,0	25
W2A09110130000	9	110-130	0,8	4,0	25
W2A09120140000	9	120-140	0,8	4,0	25
W2A09130150000	9	130-150	0,8	4,0	25

12
mm

W2B12012020000	12	12-20	1,0	6,5	100
W2B12016025000	12	16-25	1,0	6,5	100
W2B12016027000	12	16-27	1,0	6,5	100
W2B12020032000	12	20-32	1,0	6,5	100
W2B12025040000	12	25-40	1,0	6,5	100
W2B12035050000	12	32-50	1,0	6,5	50
W2B12040060000	12	40-60	1,0	6,5	50
W2B12050070000	12	50-70	1,0	6,5	50
W2B12060080000	12	60-80	1,0	6,5	50
W2B12070090000	12	70-90	1,0	6,5	25
W2B12080100000	12	80-100	1,0	6,5	25
W2B12090110000	12	90-110	1,0	6,5	25
W2B12100120000	12	100-120	1,0	6,5	25
W2B12110130000	12	110-130	1,0	6,5	25
W2B12120140000	12	120-140	1,0	6,5	25
W2B12130150000	12	130-150	1,0	6,5	25
W2B12140160000	12	140-160	1,0	6,5	25
W2B12150170000	12	150-170	1,0	6,5	25
W2B12160180000	12	160-180	1,0	6,5	25
W2B12170190000	12	170-190	1,0	6,5	25
W2B12180200000	12	180-200	1,0	6,5	25