



LASTRA TECNICA TELATA RUBBER SHEET FOR LOADING POINTS

Prodotto in conformità alle norme / Produced according to
DIN 22102



- **ESTREMAMENTE RESISTENTE A FLESSIONI E SOLLECITAZIONI**
EXTREMELY RESISTANT TO FLECTIONS AND STRESSES
- **FORNIBILE ANCHE LA VERSIONE FDA**
AVAILABLE ALSO THE FDA VERSION



CAMPI D'IMPIEGO APPLICATIONS

- Qualsiasi zona di carico e scarico degli stabilimenti
- All areas for loading and unloading platforms



DESCRIZIONE DESCRIPTION

UNIDOOR è una lastra tecnica telata utilizzata come sigillante a chiusura delle zone di carico e scarico stabilimenti. Le caratteristiche fisico meccaniche della gomma e dei tessuti impiegati all'interno del nucleo permettono al prodotto di resistere a sollecitazioni e flessioni.

UNIDOOR is a rubber sheet with textile that it's used for door-sealing system for loading and unloading platforms. The mechanical characteristics of rubber and special fabrics used in the carcass allow the UNIDOOR to withstand the constant stress and deflection during the contact with the lorries.



TIPO TYPE		
	m	mm
A	17,5	700
B	17,5	1000
C	17,5	1000

TIPO TYPE							
			mm	kg/cm²	kg/mq	%	mm³
UNIDOOR A	2 M80 Rigido Rigid	Impr. Tela Textile impression	4,0	160	1,15	450%	90
UNIDOOR B	1 EP100 Flessibile Flexible	Impr. Tela Textile impression	4,0	100	1,15	450%	90
UNIDOOR C	2 EP100 Flessibile Flexible	Impr. Tela Textile impression	4,0	200	1,15	450%	90



Fornibile anche con nastro di colore VERDE per il contatto con i generi alimentari/ingredienti (rif. norme FDA, doc. 21 CFR c1 par. 177.2600).

For food processing environments we can provide you the UNIDOOR GREEN, which can come into contact with food / ingredients as FDA, docum. 21 CFR c1, section 177.2600.



**700 mm
1000 mm**


